



## F21 Transmitter (only) 6 Buttons Single Speed

### Key features

- 3 Year Warranty, Customer Support and Service in the USA

F21 Transmitter (only) 6 Buttons Single Speed

## Technical Specifications

FCC ID	2AZMK-Q1212	Transmitter Power	≤10dBm
Transmitter Power Supply	2 AA batteries	Wireless Frequency Range	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Material	Glass-Fiber PA	IEC Motor Protection	IP65
Control Distance	Approx 100m (200 meters is customized)	Operating Temperature Range	-40 ~ 185 °F / -40 ~ 85°C
Safety Code	32 bits (4.3 billion)	Warranty	3 Year



**MODEL: F21-E2**  
**ITEM CODE: 921-006-002**  
**Dimensions: 156 x 61 x 51 mm**  
**Weight: 255g (without batteries)**

### Product Features:

- 8 operation buttons, 6 single-speed buttons and "STOP"
- 8 control contactors.
- With battery voltage warning device, the power supply is cut off during low power.
- Program the button function by computer interface.
- Up/Down, East/West, North/South can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

### Standard Configuration:

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- Operation and maintenance manual.

### Standard Configuration:

1. Unique 32 bits ID Code
2. Hamming code
3. Enhanced watch-dog circuit
4. With FCC and CE certificate



## Unit Weight & Dimensions

<b>Total Unit Weight</b>	1 lbs / 1 Kg
--------------------------	--------------

## Packaging Weight & Dimensions

<b>Package 1 Net Weight</b>	1 lbs / 0 Kg
-----------------------------	--------------

<b>Package 1 Width</b>	4 in / 10.16 cm
------------------------	-----------------

<b>Package 1 Gross Weight</b>	1 lbs / 0 Kg
-------------------------------	--------------

<b>Package 1 Height</b>	4 in / 10.16 cm
-------------------------	-----------------

<b>Package 1 Length</b>	9 in / 22.86 cm
-------------------------	-----------------