



## 1/2 Ton Mini Electric Chain Hoist 1100 Lb 10 ft Chain 110V

### Key features

- Features a compact and lightweight design, ideal for intermittent lifting of loads.
- Lifting capacity of 1100lb @ 10ft/min.
- Includes a quick-acting electromagnetic brake, emergency stop, safety key, and upper limit switch.
- 1 Year Warranty, Customer Support and Service in the USA

### Mini Electric Chain Hoist 1100 Lb 10 ft Chain 110V Description

The **Prowinch 1/2 ton Mini Electric Chain Hoist** allows you to easily lift light to medium loads. The single-phase electrical connection allows for quick and simple setup and is perfect for use in a wide variety of situations.

## Technical Specifications

|                                |                       |                        |                           |
|--------------------------------|-----------------------|------------------------|---------------------------|
| <b>Rated Load Capacity</b>     | 1100 lb / 500 kg      | <b>Control Voltage</b> | 110V                      |
| <b>Standard Lifting Height</b> | 10 ft / 3 m           | <b>Emergency Stop</b>  | YES                       |
| <b>Speed /min</b>              | 10 ft / 3 m           | <b>Contactors</b>      | HSIN DA 20 AMP            |
| <b>Number of Speeds</b>        | 1 Speed               | <b>Gear Ratio</b>      | 137:1                     |
| <b>Voltage</b>                 | 1 Phase 110~120V 60Hz | <b>Load Chain Type</b> | G80                       |
| <b>Duty Class</b>              | H1/M2/1Cm/Class A     | <b>Load Chain Size</b> | 1/4 in   6.3 mm           |
| <b>Motor/Engine Power</b>      | 720 Watts             | <b>Chain Falls</b>     | 1                         |
| <b>Motor AMP</b>               | 7                     | <b>Chain Length</b>    | 10 ft / 3 m               |
| <b>Motor Brake</b>             | Yes                   | <b>Humidity</b>        | <85%                      |
| <b>Insulation Grade</b>        | B                     | <b>Temperature</b>     | -4 ~ 104° F / -20 ~ 40° C |
| <b>IEC Motor Protection</b>    | IP40                  | <b>Noise Level</b>     | 80 dB                     |
| <b>Control</b>                 | Pendant Control       | <b>Warranty</b>        | 1 Year                    |

## Unit Weight & Dimensions

|                          |                |                               |                  |
|--------------------------|----------------|-------------------------------|------------------|
| <b>Total Unit Weight</b> | 48 lbs / 22 Kg | <b>Package 1 Net Weight</b>   | 48 lbs / 22 Kg   |
|                          |                | <b>Package 1 Width</b>        | 13 in / 33.02 cm |
|                          |                | <b>Package 1 Gross Weight</b> | 46 lbs / 21 Kg   |
|                          |                | <b>Package 1 Height</b>       | 14 in / 35.56 cm |
|                          |                | <b>Package 1 Length</b>       | 19 in / 48.26 cm |

## Packaging Weight & Dimensions