



2 Speed 1/2 Ton Electric Chain Hoist 20 ft. FEC G80 Japan Chain M5/H4 208~240/440~480V Wireless

Key features

- UL Certification, US and EU Standards ASME HST-1, ASME B30.16, EN14492-2, EN60204-32
- German Brand Schneider Contactors, All ways Limit Switches, Emergency Stop
- Overload Protection and Super Heavy Duty FEC G80 Chain, MADE IN JAPAN. Standard ASTM A973
- Quality is inside: Heavy Duty H4/M5, Aluminum Housing, NSK Bearings, USA Chevron Meropa 320 Lube
- 3 Year Warranty, Customer Support and Service in the USA

Electric Chain Hoist Description

The Wireless 2 Speed Prowinch 1/2 ton Electric Chain Hoist allows you to easily lift loads with a powerful motor. The three-phase connection makes this chain hoist perfect for use in a wide variety of situations and environments. The quick-connect wiring system allows you get set up and started on your project in no time at all.







Technical Specifications

Rated Load Capacity	1100 lbs / 500 kg	Control Voltage	12V
Standard Lifting Height	20 ft / 6 m	Emergency Stop	Yes
Speed /min	2.6 / 8 min/m	Load Chain Type	G80 JAPAN
Number of Speeds	2 Speed	Load Chain Size	6.3x19mm
Voltage	3 Phase 208~240/440~480V 50/60Hz	Chain Falls	1
Total Power Watts	900	Chain Length	20 ft / 6 m
FCC ID	2AZMK-Q1212	Humidity	<85%
Duty Class	H4/M5/2m/Class D	Temperature	-4 ~ 104° F / -20 ~ 40° C
Motor/Engine Power	0.9 KW	Noise Level	81 dB
Motor Brake	Yes	Standards Compliance	UL 1340 - ASME HST-1 , ASME B30.16, EN60204-32
Insulation Grade	F	UL File	MSXT.E528915 - Hoists
IEC Motor Protection	IP55	Warranty	3 Year
Control	Wireless F21-4 and Pendant Control		







Unit Weight & Dimensions

H Minimum Headroom 17.9 in / 45.5 cm W Width 18.1 in / 45.8 cm D Depth 9.1 in / 22.9 cm J Hook Opening 1.46 in / 3.7 cm Total Unit Weight 93 lbs / 43 Kg

Packaging Weight & Dimensions

Package 1 Net Weight	93 lbs / 42 Kg
Package 1 Width	19 in / 48.26 cm
Package 1 Gross Weight	123 lbs / 56 Kg
Package 1 Height	18 in / 45.72 cm
Package 1 Length	24 in / 60.96 cm