

2 Ton Electric Chain Hoist Power Trolley 20 ft FEC G80 Japan Chain M5/H4 3 Phase Wireless


Key features


- UL 1340 File No E528915, ASME HST-1 , ASME B30.16 , EN14492-2 , EN60204-32
- Heavy Duty H4/M5 Aluminum housing, NSK Bearings, USA Chevron Meropa 320 Lube
- Overload Protection and Super Heavy Duty FEC G80 Chain, MADE IN JAPAN. Standard ASTM A973
- German Brand Schneider Contactors, All ways Limit Switches, Emergency Stop
- 3 Year Warranty, Customer Support and Service in the USA

2 Ton Electric Chain Hoist Power Trolley 20 ft FEC G80 Japan Chain M5/H4 3 Phase Wireless

Technical Specifications

Rated Load Capacity	4400 lbs / 2000 kg	**Emergency Stop**	Yes
Standard Lifting Height	20 ft / 6 m	**Load Chain Type**	G80 JAPAN
Speed /min	26 ft	**Load Chain Size**	11.2 x 34 mm
Number of Speeds	1 Speed	**Chain Falls**	1
Voltage	3 Phase 208~240/440~480V 50/60Hz	**Chain Length**	20 ft / 6 m
FCC ID	2AZMK-Q1212	**Humidity**	<85%
Duty Class	H4/M5/2m/Class D	**Temperature**	-4 ~ 104° F / -20 ~ 40° C
Motor/Engine Power	3 kW	**Noise Level**	81 dB
Motor Brake	Yes	**I-Beam Width Range**	5 - 7 inches
Insulation Grade	F	**Standards Compliance**	UL 1340, ASME HST-1 , ASME B30.16 , B30.17, EN60204-32
IEC Motor Protection	IP55	**UL File**	MSXT.E528915 - Hoists
Control	Wireless PW-Q400 and Pendant Control	**Warranty**	3 Year
Control Voltage	24V		





Unit Weight & Dimensions

T Trolley Motor Width	6.9 in /16.5 cm
W Width	27.5 in / 69.4 cm
H Minimum Headroom	23 in / 57.5 cm
J Hook Opening	1.53 in / 3.9 cm
D Depth	14 in / 35 cm

Packaging Weight & Dimensions

Package 1 Gross Weight	364 lbs / 165 Kg
Package 1 Width	25 in / 63.5 cm
Package 1 Length	29 in / 73.66 cm
Package 1 Height	38 in / 96.52 cm