



500 Lb Mini Electric Chain Hoist 20 ft Chain H3 110V UL Certified

Key features

- High quality Hoist with UL Certification
- Overload Protection and Heavy Duty, Durable G80 Chain
- Key safety features such as all-way limit switches, emergency stop, and automatic brake system.
- Meets US and EU Standards ASME HST-1, ASME B30.16, EN14492-2, EN60204-32.
- 3 Year Warranty, Customer Support and Service in the USA

Mini Electric Chain Hoist Description

The Prowinch 550 lb **UL Certified Mini Electric Chain Hoist** allows you to easily lift loads. The powerful motor and single phase electrical connection are perfect for use in a wide variety of situations and environments. The integrated wireless control offers added convenience with the ability to operate the hoist from up to 100 feet away.

UL Certified Electric Chain Hoist

All of our **Electric Chain Hoists** are created with the goal of offering the best price-performance ratio. Key components such as lifespan factors are constantly tested and improved in order to offer the best product for the price.

Key Components

All internal components have been upgraded to meet the highest quality standards. Key electronic components are produced by American or German brands, and we use American-made lubricants to ensure the lifespan of gears and reducers. Final assembly and all tests are performed in the US before shipping to ensure that every unit meets the corresponding standard.

Duty Classification

Duty classification is a key factor when choosing the right unit. These H3 hoists are suitable for general machine shop fabricating, assembly, storage, and warehousing. For uniformly distributed work periods, the hoists have 25% max. operational time per hour and can handle up to 150 starts per hour. When being used for infrequent work periods, the hoist can be operated for 30 minutes from a cold start with up to 200 starts per hour. Operational time ratings are calculated at a 65% load factor, as per ASME HST-1-2012.

Control System



This **Electric Chain Hoist** comes with a pendant control with up, down, and emergency stop. The length of the pendant control is 4 feet less than the lifting height, which allows it to be easily operated from ground-level.

Braking System

The **electromagnetic brake system** is tested at 125% of the hoist capacity and is designed to automatically engage immediately upon any loss of power.

Technical Specifications

| | | | |
|--------------------------------|-----------------------|-----------------------------|--|
| Rated Load Capacity | 500 lbs / 226 kg | Control Voltage | 24V |
| Standard Lifting Height | 20 ft / 6 m | Emergency Stop | Yes |
| Speed /min | 7 ft / 2.1 m | Load Chain Type | G80 |
| Number of Speeds | 1 Speed | Load Chain Size | 5 x 15 mm |
| Voltage | 1 Phase 110~120V 60Hz | Chain Falls | 2 |
| Total Power Watts | 130 | Chain Length | 20 ft / 6 m |
| Duty Class | H3/M4/1Am/Class C | Humidity | <85% |
| Motor/Engine Power | 0.17 kw | Temperature | -4 ~ 104° F / -20 ~ 40° C |
| Motor Brake | Yes | Noise Level | 81 dB |
| Insulation Grade | F | Standards Compliance | UL 1340 - ASME HST-1 , ASME B30.16, EN60204-32 |
| IEC Motor Protection | IP55 | UL File | MSXT.E528915 - Hoists |
| Control | Pendant Control | Warranty | 3 Year |



Unit Weight & Dimensions

| | |
|---------------------------|-----------------|
| H Minimum Headroom | 16.2 in / 41 cm |
| W Width | 14.1 in / 36 cm |
| D Depth | 6 in / 15 cm |
| J Hook Opening | 1 in / 2.6 cm |

Packaging Weight & Dimensions

| | |
|-------------------------------|------------------|
| Package 1 Gross Weight | 60 lbs / 27 Kg |
| Package 1 Width | 15 in / 38.1 cm |
| Package 1 Length | 18 in / 45.72 cm |
| Package 1 Height | 18 in / 45.72 cm |