

10 Ton Power Trolley 220/460V 60HZ 3 Phase with Limit Switches Pendant not Included

Key features


• 3 Year Warranty, Customer Support and Service in the USA


10 Ton Power Trolley 230/460V 60HZ 3 Phase with Limit Switches Pendant not Included



Technical Specifications

Rated Load Capacity	22000 lb / 10000 kg	I-Beam Width Range	5.9~8.6 in / 150~220 mm
Voltage	3 Phase 208~240/440~480V 50/60Hz	Minimum Turn Radius	6.56 ft / 2 m
Total Power Watts	0.75 kW	Standards Compliance	ASME B30.17
Trolley Speed /min	43 ft / 13 m @ 60 HZ 36 ft / 11 @ 50 HZ	Warranty	3 Year





Model /	Modelo	PWQE1Ti	PWQE2Ti	PWQE3Ti	PWQE5Ti	PWQE7Ti	PWQE10Ti
_ s	w	12.4 in / 315mm	12.7 / 325mm	13.3in / 340mm	15.7 in/ 400mm	26.5 in / 670 mm	19.6in / 500mm
Dimensions / Dimensiones	U	8.3 in / 212mm	8.6mm / 220mm	9.8 in / 250mm	11.4 in / 291mm	-	14.6in / 371mm
	R	5.5 in / 142mm	5.5 in / 142mm	5.5 in / 142mm	5.5 in / 142mm	9 in / 231 mm	5.5 in / 142mm
	Т	9 in / 231mm	9 in / 231mm	9 in / 231mm	9 in / 231mm	5.6 in / 142 mm	9 in / 231mm

Unit Weight & Dimensions

Packaging Weight & Dimensions

T Trolley Motor Width	9.09 in / 231 mm	Package 1 Net Weight	270.6 lbs / 123 Kg
A Total Height	8.5 in / 212 mm	Package 1 Width	21 in / 53.34 cm
R Trolley Cover Width	6 in / 142 mm	Package 1 Gross Weight	290.4 lbs / 132 Kg
W Width	12 in / 315 mm	Package 1 Height	21 in / 53.34 cm
Total Unit Weight	270.6 lbs / 123 Kg	Package 1 Length	25 in / 63.5 cm

