



Heavy Duty 5 Ton Capacity Manual Chain Trolley 10000 lb Geared

Key features

• 3 Year Warranty, Customer Support and Service in the USA

Gearing provides positive load positioning along the beam. Light-weight trolleys fit most I-, S-, and W-beams. 5 ton geared trolley Designed with durable baked enamel paint protection and precision ball bearing wheels. With a manual-chain operated gear trolley for use on overhead equipment beyond operator's reach, low headroom for work in tight spaces, and steel construction for strength. The trolley fits a range wide flange or S-type I-beams. Assembly required.

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com






4.3 ft / 1.5 m


Technical Specifications



I-Beam Width Range

11000 lb / 5000 kg 4-7 in / 100-200 mm





Minimum Turn Radius

Model / Modelo		PWQMC05T	PWQMC1T	PWQMC3T	PWQMC5T	PWQMC10T	PWQMC20T
Dimensions / Dimensiones	A	9.8 in / 250 mm	10.2 in / 260 mm	13 in / 330 mm	14.6 in / 370 mm	15.7 in / 400 mm	16.9 in / 430 mm
	В	7.7 in / 195 mm	8.3 in / 210 mm	11.8 in / 300 mm	13.7 in / 334.5 mm	18.1 in / 460 mm	22.8 in / 580 mm
	С	7.1 in / 180 mm	7.9 in / 200 mm	9 in / 228.5 mm	13.7 in / 334.5 mm	19.3 in / 490 mm	19.7 in / 500 mm
	Н	3.5 in / 90 mm	3.7 in / 95 mm	5.5 in / 140 mm	6.7 in / 170 mm	10.8 in / 275 mm	11 in / 280 mm

Unit Weight & Dimensions

Total Unit Weight

90 lbs / 41 Kg

Packaging Weight & Dimensions

Package 1 Net Weight	90 lbs / 41 Kg
Package 1 Width	14 in / 35.56 cm
Package 1 Gross Weight	92 lbs / 42 Kg
Package 1 Height	13 in / 33.02 cm
Package 1 Length	9 in / 22.86 cm

Prowinch LLC Certified under Standard Quality Management Systems ISO 9001 info@prowinch.com

